



## Delta TRV 25



Delta TRV 25

### **Meeting quality requirements by sorting**

The purpose of the vibrating sorting table is:

- to spread out the crop,
- to ensure separation of grapes from juice and herbaceous materials (damaged grapes, petioles, shot berries, etc.),
- to allow regular feeding to the next equipment in the processing line (automatic sorting line, pump, crusher, etc...).

Grapes are placed at one end of the table and travel towards the other end of the table by microvibration.



Vibrating intermediate grid



Elimination of undesirable materials

## Description

The sorting table is delivered with:

- 1 glass-blasted stainless steel table linked to the frame via 4 silent blocks.
- 2 removable draining grids:
  - with trapezoidal bars, choice between 4, 6 or 8 mm spacing. Trapezoidal shape allows the evacuation of juices and herbaceous materials.
  - or with perforations 2 x 20 mm for the evacuation of juices.
- 1 vibrating intermediate grid, perforations 2x20mm (located under top dejuicing grid) for the removal of MOG from juice.
- 1 tray to collect free juices with an opening on either side (right or left).
- 4 stainless steel wheels equipped with brakes and adjustable stands to ensure a perfect stability.
- 2 motors with frequency variator.

## Options

- Reception hopper for tray of 400 kg.
- Frame with height of 1, 5 m or 2 m.
- High capacity hopper.

## Technical characteristics

- Flow rate of 20 to 25 T/h (depending on grape varieties, condition and grapes nature).
- 2 vibrating units of 1, 6 Kw each.
- 80 mm profiled tube framework.
  
- Delta TRV 25:
  - Length: 2550 mm
  - Height: 1360 mm
  - Width: 900 mm (1315 mm overall)

Distributed by:

### Bucher Vaslin

Rue Gaston Bernier - BP 70028  
F - 49290 Chalonnes sur Loire  
Tél. +33 (0)2 41 74 50 50  
Fax +33 (0)2 41 74 50 51  
E-mail : [commercial@buchervaslin.com](mailto:commercial@buchervaslin.com)

[www.buchervaslin.com](http://www.buchervaslin.com)  
Your success is our priority

Video :

