

Bucher Origin CF

Length	3500	3800	4190	4940	4430	5170
Width	1590	1630	1970	1970	2150	2150
Height	2090*	2170*	2120*	2120*	2240**	2240**

Options

Must pump warning

Must pump control with retractable level probe device when sliding the screen



Axial filling

With manual valve



Other options

Router
Add-ons
Spacers
Fixed or mobile filling hoppers

The benefits

Adaptability

The Bucher Origin pneumatic press has wide-opening doors for quality filling of the press and easy emptying of the pomace. Its sliding screen ensures juice collection and easy access for washing.

Programming is user-friendly, using a touch-sensitive colour PLC. As standard, the PLC includes 2 sequential programmes and 6 pre-recorded automatic programmes. The operator is free to choose the most appropriate programme and modify the holding times during pressing. The 'intelligent' OFM programme is used to optimise holding times. This programme offers the possibility of automatically switching from one stage to another when flow rates are low, thereby reducing pressing times.

Washing

Cleaning the Bucher Origin pneumatic press is quick and easy. A rear hatch provides effortless access to the underside of the press to ensure wash water drains completely. The large door opening makes it easy to clean the inside of the tank. The press is also fitted with quick-fit drains that can be swivelled without the need for tools, for optimal washing. There is also a rinsing ramp for the outside of the tank.

Operator safety

The Bucher Origin press is equipped with cables all around the press to stop the machine as soon as the operator leans on it.

The press is equipped with a "door close" safety device before the tank is pressurized.

Bucher Vaslin North America

3100 Dutton Avenue Suite 134D
Santa Rosa, CA 95407
(707) 823-2883

